

4 IN 1 IR SPEED DOME: HD-S2PTZ20X/HD-S5PTZ20X

- * OSD menu is available
- * Keep original analog system
- * AHD/TVI/CVI/CVBS selectable
- * 4.5" Total metal body construction
- * Real time transmission ,lossless video
- * Long distance transmission up to 500 meters



Camera		
Solution	1/3" CMOS 2MP SONY323	1/3" CMOS 5MP OV05A10
Output pixel	1920x1080p/30fps 1920x1080p/25fps	2592x1944@15fps 2592x1520@22fps
Lens	20X 4.7mm~96.3mm	
Dome		
Rotation Range	Pan: 0°~360° , Tilt: 0°~93°	
Medium rotation speed	Pan: 0~80°/s , Tilt:0~40°/s	
Auto Flip	Horizontal 180°, Vertical 93°	
Preset Points	220pcs preset(Dwell time 01-60s interval available)	
A-B Scan	User programmable (scan speed 1-64 levels setting available)	
Guard Tours	3 groups (Max.16 points, dwell time user selectable)	
PWR On Action	Memory/Tour 1/360° scan/A-B scan/Park 1/None	
Video interface output	AHD/TVI/CVI/CVBS selectable	
Communication mode	RS485 (+/-) / coaxial cable	
Operating Temperature	-40°C~+60°C	
Power	DC12V 3A	
Power Consumption	≤ 25W	
IR distance	60 meters	
LEDs	6PCS Array 42Mil IR LED	